

Magshell 900



Manual swipe, bi-directional magnetic reader, conforms to ISO 7810, 7811, AAMVA, JIS & DMV format, All ISO tracks supported. Communicates with a host computer or other terminal via a standard Universal Serial Bus (USB) interface

Features

- Buzzer and LED indicator
- Read and convert RS232 magnetic data
- Bi-Directional
- All ISO tracks supported
- (USB) interface, no external power required
- Fully portable
- Small footprint

Technical specifications

Interface	USB Full Speed (1.1)
Scanner Weight	20 oz / 210gr.
Dimensions (LxWxH)	3.94"/100mm L x 1.1"/28mm H x 1.33"/34mm W
Power consumption	USB powered (2.0 W @ 5Vdc)
Operating Voltage	+5VDC +/- 10%, 110mA max
Certifications	CE, FCC, UL, cUL
ISO	ISO track 1, 2 and 3, 7810, 7811, AAMVA, JIS & DMV format

Electrical		Performance		
Power	+5VDC ± 10% from USB port	Read card	ISO 7810, 7811/1-6/AAMVA, custom data	
Consumption	98mA max. in normal condition	Coercive force	Read 300-4000, Ce Magnetic Card	
Communication	Standard RS232 to USB	Read speed	STD card	Jitter ± 15%
			5-55 ps	5-50 ps
			Amp 60%	5-50 ps
Mechanical		Read error rate	<0.5%	
Body material	ABS 04V-0	Environment		
Dimension	3.94"/100mm L x 1.1"/28mm H x 1.33"/34mm W	Operation	-10 to 550C, 10 to 90% Humidity	
Weight	20 oz / 210gr.	Storage	-30 to 700C, 10 to 90% Humidity	
Connection	USB series "A" plugs	Agency approval		
		FCC/CE class A UL, cUL		
Handling Method	Manual, swipe, bi-directional			

For more information:
Card Scanning Solutions
6167 Bristol Parkway
Suite 330
Culver City, CA 90230
(213) 867-2625
Mon-Thu 07:00 to 5:00 PST
and Fri 07:00 to 4:00 PST
Fax: (419) 735-2419
www.card-reader.com